

Unano P1.8 8:9 423mm x 498mm

SKU: LV1676 Model: Unano P1.8 8:9 423mm x 498mm

Parameter Parame		Unit	Value
Display technology	Pixel Pitch	mm (inch)	1.8
	Brightness	nits	800
	Viewing Angle - Horizontal	deg.	160
	Viewing Angle - Vertical	deg.	160
	Pixel Type & Configuration	RGB	3-in-1 SMD
	Resolution per Cabinet	-	240(w) x 270(h)
	Dot per Cabinet	-	64800
	Dot per sq. Meter	-	293769
	Colours	-	16.5 million
	Grey Scale (linear)	Levels	65,365 levels per colour
	Contrast Ratio	-	5000:1
	Display Refresh Rate	Hz	1920
	BTU's	sq m/hour	103
Physical	Cabinet Width	mm (inch)	422.8 (16.64567828)
	Cabinet Height	mm (inch)	498.15 (19.612215315)
	Cabinet Depth	mm (inch)	62 (2.4409462)
	Cabinet Weight	Kg	7
	Cabinet Area	Sq. m.	0.2206
	Cabinet Material	-	Die-cast aluminum
	Cabinet Type	-	Indoor - rental and staging
	Recommended Minimum Viewing Distance	m	1.8
	Recommended Best Viewing Distance	m	2.8
	Mounting System	Hanging or 4x8mm bolts (m8)	
Environment	Operating Temperature Range	deg. C	0 - 50
	Humidity Operating Range	RH	10 -90
	Lifetime	Hours	100,000
Power	Input Voltage (nominal)	VAC	120
	Power Draw	W/Cabinet Avg (Max)	Unable to pull dynamic data please contact your sales re
	Current (120V @ 60Hz)	Amps Avg (Max)	Unable to pull dynamic data please contact your sales re
Warranty	Manufactured	Manufactured in China	
	Warranty	year manufacturers warranty on part defects. LIGHTVU extended warranty up to years.	
Certifications	CEC Certification	CE, FCC, RoHS, cETL	



