



Unano P1.3 8:9 423mm x 498mm

SKU: LV1677 Model: Unano P1.3 8:9 423mm x 498mm

| Parameter | Unit | Value | |
|--------------------------------------|-----------------------------|---|--|
| Display technology | Pixel Pitch | mm (inch) | 1.3 |
| | Brightness | nits | 600 |
| | Viewing Angle - Horizontal | deg. | 160 |
| | Viewing Angle - Vertical | deg. | 160 |
| | Pixel Type & Configuration | RGB | 3-in-1 SMD |
| | Resolution per Cabinet | - | 320(w) x 360(h) |
| | Dot per Cabinet | - | 115200 |
| | Dot per sq. Meter | - | 591360 |
| | Colours | - | 16.5 million |
| | Grey Scale (linear) | Levels | 65,365 levels per colour |
| | Contrast Ratio | - | 5000:1 |
| | Display Refresh Rate | Hz | 1920 |
| | Physical | Cabinet Width | mm (inch) |
| Cabinet Height | | mm (inch) | 498.15 (19.612215315) |
| Cabinet Depth | | mm (inch) | 62 (2.4409462) |
| Cabinet Weight | | Kg | 7 |
| Cabinet Area | | Sq. m. | 0.2206 |
| Cabinet Material | | - | Die-cast aluminum |
| Cabinet Type | | - | Indoor - rental and staging |
| Recommended Minimum Viewing Distance | | m | 1.3 |
| Recommended Best Viewing Distance | | m | 2.3 |
| Environment | Mounting System | Hanging or 4x8mm bolts (m8) | |
| | Operating Temperature Range | deg. C | 0 - 50 |
| | Humidity Operating Range | RH | 10 -90 |
| Power | Lifetime | Hours | 100,000 |
| | Input Voltage (nominal) | VAC | 120 |
| | Power Draw | W/Cabinet Avg (Max) | Unable to pull dynamic data, please contact your sales rep |
| Warranty | Current (120V @ 60Hz) | Amps Avg (Max) | Unable to pull dynamic data, please contact your sales rep |
| | Manufactured | Manufactured in China | |
| Certifications | Warranty | year manufacturers warranty on part defects. LIGHTVU extended warranty up to years. | |
| | CEC Certification | CE, FCC, RoHS, cETL | |



Due to constant research and product development, specifications subject to change without notice.

