



Aurora P4 Window Poster - 768x1280 High Bright
 SKU: LV0962 Model: LV-IWRF-P4-768/1280-0V6-1NHB

Parameter	Unit	Value		
Display technology	Pixel Pitch	mm (inch)	4	
	Brightness	nits	4500	
	Viewing Angle - Horizontal	deg.	160	
	Viewing Angle - Vertical	deg.	95	
	Pixel Type & Configuration	RGB	3-in-1 SMD	
	Resolution per Cabinet	-	192(w) x 320(h)	
	Dot per Cabinet	-	61440	
	Dot per sq. Meter	-	62500	
	Colours	-	16.5 Million	
	Grey Scale (linear)	Levels	65,536 levels per color	
	Contrast Ratio	-	10000:1	
	Display Refresh Rate	Hz	1920	
	Physical	Cabinet Width	mm (inch)	778 (30.6299378)
		Cabinet Height	mm (inch)	1290 (50.787429)
Cabinet Depth		mm (inch)	90 (3.543309)	
Cabinet Weight		Kg	33	
Cabinet Area		Sq. m.	0.983	
Cabinet Material		-	Aluminum / steel	
Cabinet Type		-	Indoor - fixed installation	
Recommended Minimum Viewing Distance		m	4	
Recommended Best Viewing Distance		m	5	
Mounting System		4 x M8 bolts. all active components fully front serviceable		
Environment	Operating Temperature Range	deg. C	5 - 50	
	Humidity Operating Range	RH	10 - 90	
	Lifetime	Hours	100,000	
Power	Input Voltage (nominal)	VAC	120	
	Power Draw	W/Cabinet Avg (Max)	420 (1176)	
	Current (120V @ 60Hz)	Amps Avg (Max)	3.5 (9.8)	
Warranty	Manufactured	Designed and manufactured in Canada		
	Warranty	year manufacturers warranty on part defects. LIGHTVU extended warranty up to years.		
Certifications	CEC Certification	CE FCC RoHS cETL		
Heat	Full Brightness, Average Content	BTU	537	
	Full Brightness, Full White Content	BTU	1612	
	Half Brightness, Average Content	BTU	242	
	Half Brightness, Full White Content	BTU	725	



Due to constant research and product development, specifications subject to change without notice.

